


DRIVE

Drive 1" vulcanized composition rubber molded tiles are engineered to provide support, durability, and superior noise and shock absorption. Drive tiles are designed to withstand heavyweight impacts and are easy to install.



PRODUCT & COLOR OPTIONS

- 24" x 24" tile, 1" thick
- Easy installation with Quad Blok installation system



Proprietary Installation System
Quad Blok

- Available 12 colors

PHYSICAL DATA

Performance Criteria	Density	Test Method	Typical Results
Static Load Limit		ASTM F970	0.005" (@400psi)
Coefficient of Friction		ASTM D2047	>0.9
FloorScore		CA01350	Certified
Abrasion Resistance		ASTM D3389	<1g, 1,000 cycles
Pill Test		ASTM D2859	Pass
Impact Insulation Class IIC*		ASM E492	56
Delta IIC*		ASTM E2179	27

PRODUCT FEATURES

- Sound and shock absorbent
- Slip resistant, wet or dry
- Durable
- Easy to install with Quad Blok

APPLICATIONS

- Playgrounds
- Fitness Areas
- Heavy Equipment Areas
- Free Weight Areas
- Dumbbell Areas
- Home Gyms



FORCE REDUCTION 50.2%



ENERGY RESTITUTION 47.9%

*Tested on a 6" concrete slab with no ceiling.

INSTALLATION FAST FACTS

- May be installed over most concrete, wood, or tile
- Floor must be level, in good condition and clear of dirt and loose debris
- Dry laying and full inspection of all tiles will allow for a quality installation