

TWEED & TWILL WOVEN VINYL

Tweed & Twill feature sophisticated 1mm woven vinyl surface layers factory fusion bonded to a 5mm vulcanized composition rubber base layer that provides safety, ergonomic, and acoustic benefits. The color line features two distinct visuals that can be coordinated together to be used in the same space.



PRODUCT & COLOR OPTIONS

- 6mm x 6' wide roll
- Tweed & Twill are available in 6 colors each and are suggested to be used in combination with each other.



FORCE REDUCTION 12.0%



ENERGY RESTITUTION 69.0%

PRODUCT FEATURES

- Durable
- Stain Resistant
- Ergonomic
- Quiet Underfoot

APPLICATIONS

- Retail/Offices
- Cardio
- Home Gyms
- Physical Therapy
- Group Exercise

PHYSICAL DATA

Performance Criteria Density	Test Method	Typical Results
Static Load Limit (@250psi)	ASTM F970	0.006"
Coefficient of Friction	ASTM D2047	0.8 dry
Flammability (Critical Radiant Flux)	ASTM E648	Class 1
Flammability (Pill Test)	ASTM D2859	Pass
Dynamic Rolling Load	ASTM F2753	Pass
Resistance to Light	ASTM F1515	Pass
Resistance to Heat	ASTM F1514	Pass
G-Max	Clegg	343 avg.
Thermal Conductivity	ASTM C51	0.9 Btu-in/hr-ft ² -F
Impact Insulation Class (IIC)*	ASTM E492	55
Delta IIC*	ASTM E2179	23
Airborne Sound Transmission (STC)*	ASTM E90	53

*Tested on a 6" concrete slab with no ceiling.

Note: It is normal for Tweed & Twill to exhibit light and dark shade variation at seams and roll to roll. See the Technical Manual for more details.