

General cleaning after floor installation

1. Remove large construction residue
2. Dust mop and remove dirt and dust
3. Inspect the floor for any dirt stains and adhesive residue.
4. Remove adhesive residue using approved cleaning method
5. Damp mop floor with clean diluted floor detergent.

Facility initial cleaning (Task should be performed by professional floor cleaners)

EcoFlor coverings have a production residue. This residue should be removed before the flooring is used, otherwise it will attract dust and dirt. EcoFlor coverings have a natural sheen; therefore they do not require any artificial coating.

General Remarks

General Precautions

1. Always use "wet floor" signs and/or caution tape when performing any wet cleaning.
2. Refer to MSDS for proper personnel protection requirements before using cleaning products.
3. Do not flood the floor.
4. The floor will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and any foreign materials.
5. Never use grit brushes, black or brown pads.
6. Make sure to maintain a good walk-off area in the entrance of the facility, in addition to regular dust mopping.
8. Spots from petroleum-based products such as grease and tar must be removed with spotting agents containing solvents. Immediately rinse with water after spot removing and allow drying.
9. Remove chewing gum with a gum removing spotter. If a solvent is used for removing gum, immediately rinse the floor with clean water, and allow drying.
10. Do not use a high speed buffing machine that exceeds 1600 rpm.
11. If required, dry buff nora® floor coverings with a synthetic white pad or carpet cotton bonnet pad.
12. Do not use a cleaning agent with a pH higher than 10.5 when diluted.
13. Do not allow any metal furniture or trash cans to be in contact with the wet floor.

Facility initial cleaning procedures shall not be performed within 72 hours of installation.

1. Dust mop or vacuum the floor to remove dirt or grit.
2. Remove any adhesive residue.
3. Wet mop the floor with JohnsonDiversey TASKI Profi™ and allow the solution a minimum dwell time of 10 minutes. Dilution — 8 ounces per gallon of lukewarm water.
4. Scrub the floor thoroughly with a floor scrubber using 3M # 5300 scrub pad.
5. Wet vacuum the soiled solution, rinse the floor with clean water and allow to dry.

Daily Maintenance

1. Dust mop or vacuum the floor to remove dust and dirt.
2. Damp mop or auto-scrub the floors with multi-purpose floor cleaner (diluted as recommended on the manufacturer's label) and allow to dry.

Periodic Maintenance

1. Dust mop or vacuum the floor to remove dust and dirt.
2. If required, remove chewing gum with a gum removing spotter. If a solvent is used for removing gum, immediately rinse with clean water.
3. Wet mops the floor with JohnsonDiversey TASKI Profi™ and allow the solution a minimum dwell time of 10 minutes. Dilution — 4 ounces per gallon of lukewarm water.
4. Thoroughly scrub the floor with a floor scrubber using 3M #5300 scrub pad.
5. Wet vacuum the soiled solution, rinse the floor with clean water and allow to dry.