

Centaur Floor Systems

presents

Morado

Solid Color Rubber Roll Flooring

Wearing Surface:	1 mm. virgin rubber.
Size:	Width is 4'
Backing:	100% SBR black rubber with fabric finish bottom
Finish:	Leather Finish non-slip.
Thickness:	6.5 and 8 mm.
Colour:	Solid - Dark Grey, Red, Black, Dark Blue, Putty, Plum

MATERIAL PROPERTIES:

Test	Test Method	Test Result
Shore Hardness	ASTM 2240	80.25 (top) 71.75 (bot)
Compression Set	ASTM D395	9.93%
Taber Abrasion	ASTM C501	321.2 mg/1000 (.256 g weight loss)
Tensile Strength	ASTM D412	Top 1596.4 psi, Bottom 380.4 psi
Co-Efficient of Friction	ASTM C1028	0.93 dry, 0.84 wet
Elongation at Break	ASTM D412	334.3 Top/Bot 139.6
Tear Resistance	ASTM D624	120.8 lbs/in
Moisture Absorption	ASTM D570	0.37%
Critical Radiant Flux	ASTM E648-03	0.92
Static Load Limit	ASTM F970-00	500 psi
Optical Density of Smoke	ASTM E662	PASS

Your complete Flooring Information Source!

135 Chapala Street • Santa Barbara, CA 93101
Phone (805) 957-0182 • Fax (805) 957-0125
Toll-Free (800) 536-9007
www.centaurfloors.com

COMMUNITY CENTERS

HOTELS

ICE ARENAS

PRIVATE GYMS

FITNESS CENTERS

HIGH RISES

SCHOOLS

MULTI-TENANT PROPERTIES

SKI FACILITIES

MILITARY BASES