

# SPECKLED S & PUZZLETILE

These vulcanized composition rubber surfaces are designed for easy, fast installation. These products offer great surface solutions with outstanding durability in a cost-effective system.



## PRODUCT FEATURES

- Durable
- Sustainable
- Slip-Resistant
- Ease of Maintenance

 **FORCE REDUCTION** 9.98%

 **ENERGY RESTITUTION** 71.9%

## APPLICATIONS

- Fitness Centers
- Education
- Physical Therapy
- Home Gyms

## PRODUCT & COLOR OPTIONS

### Speckled S:

4' x 25' roll; 8mm thick  
4' x 50' roll; 8mm thick

[Click Here to View Speckled S Colors](#)

### PuzzleTile:

23" x 23" interlocking tile; 8mm thick

[Click Here to View PuzzleTile Colors](#)

## PHYSICAL DATA

Performance Criteria	Density	Test Method	Results
Static Load Limit		ASTM F970	0.020" (@ 1,000 psi)
Coefficient of Friction		ASTM D2047	>0.9
FloorScore		CA01350	Certified
Abrasion Resistance		ASTM D3389	<1g, 1,000 cycles
Pill Test		ASTM D2859	Pass
Impact Insulation Class*		ASM E492	51
Delta IIC*		ASTM E2179	22

*\*Tested on a 6" concrete slab with no ceiling.*

## INSTALLATION FAST FACTS

- 3 year warranty
- Indoor use only
- PuzzleTile is not designed to be used under rolling loads or in commercial applications, due to the loose lay design
- Install tiles over wood, concrete subfloors or firmly adhered resilient flooring such as vinyl, linoleum, laminate, ceramic tile and wood