

FASTRACK

Fastrack is a premier, multi-layer surface that provides high performance and superior durability. This product is ideal for free weights and functional training applications in home gyms.



PRODUCT & COLOR OPTIONS

Rolls:

4' x 25' roll; 14.5mm thick
4' x 50' roll; 7.5mm thick

Interlocking Tiles:

23" x 23" interlocking tile; 14.5mm thick

[Click Here to View Colors](#)



FORCE REDUCTION 35.4%

14.5mm



ENERGY RESTITUTION 53.7%



FORCE REDUCTION 12.6%

7.5mm



ENERGY RESTITUTION 66.8%

PRODUCT FEATURES

- Durable
- Sustainable
- Ease of maintenance
- Slip-resistant
- Interlocking tiles are easy to install

APPLICATIONS

- Multi-purpose Areas
- Running/walking Tracks
- Physical Therapy
- Fitness Spaces
- Retail

PHYSICAL DATA 14.5mm product

Performance Criteria Density	Test Method	Results
Static Load Limit	ASTM F970	0.009" (@250psi)
Coefficient of Friction	ASTM D2047	>0.9
FloorScore	CA 01350	Certified
Abrasion Resistance	ASTM D3389	<1g 1,000 cycles
Pill Test	ASTM D2859	Pass
Standard Vertical Deformation	ASTM F2772	2.66mm
Surface Effect Slip Resistance	ASTM F2772	Pass
Ball Rebound	ASTM F2772	98.8%
Force Reduction	ASTM F2772	35.7%
Impact Insulation Class IIC*	ASTM E492	58
Delta IIC*	ASTM E2179	27

*Tested on a 6" concrete slab with no ceiling.