

# INTERVAL TURF

Centaur has revolutionized indoor turf by fusion bonding a premium turf surface layer to a 5mm or 12mm vulcanized composition rubber base layer. The result is an ideal surface for footwork and functional training while providing cushion underfoot and sound isolating advantages.



## PRODUCT & COLOR OPTIONS

### Rolls:

6' x 25' roll; 17mm (12mm + 5mm) thick  
6' x 35' roll; 24mm (12mm + 12mm) thick

### Interlocking Tiles:

23" x 46" interlocking tile; 24mm thick

All options are available in Green, Black, Gray, and Blue

## 5mm BASE LAYER



**FORCE REDUCTION** 30.8%



**ENERGY RESTITUTION** 46.6%

## 12mm BASE LAYER



**FORCE REDUCTION** 47.1%



**ENERGY RESTITUTION** 41.0%

## PRODUCT FEATURES

- Impact reduction
- No infill required
- Portable & easy to install (Interlocking Tiles)

## APPLICATIONS

- Indoor functional training
- Speed and agility areas
- Home gyms

## PHYSICAL DATA

### Performance Criteria Density

Performance Criteria	Test Method
Force Reduction	Deltec
Energy Restitution	Deltec
Vertical Deformation	Deltec
G-Max	Clegg
Tufted Pile Height	
Pill Test / Flammability	ASTM D2859
Coefficient of Friction	ASTM D2047

### Results

	5mm	12mm
Force Reduction	30.8%	47.1%
Energy Restitution	46.6%	41.0%
Vertical Deformation	3.8mm	4.9mm
G-Max	192	84
Tufted Pile Height	0.47"	0.47"
Pill Test / Flammability	Pass	Pass
Coefficient of Friction	0.87 <sub>(dry)</sub>	0.87 <sub>(dry)</sub>

## INSTALLATION FAST FACTS

- 5 Year limited warranty
- Rolls may be installed over concrete, approved Portland-based patching and leveling materials and wood
- Interlocking Tiles may be installed over wood, concrete subfloors or firmly adhered resilient flooring such as vinyl, linoleum, laminate, ceramic tile, and wood