

PRODUCT SALES SHEET

E-TAK 99

A premium, pressure sensitive, multi-flooring adhesive and plasticizer migration blocker

Available in: 4 Gallon Pail

Type: One-part Acrylic PSA

Works with: LVT, 2mm Sheet Vinyl, Sound Control Underlayment [Sound Reducer]



	Maximum RH (per ASTM F-2170)	Substrate pH	Flash Time*	Working Time*	Shelf Life	Freeze/Thaw Stability	Antimicrobial	Trowel	Spread Rate
Tacky/Wet Pressure Sensitive Installations [Luxury Vinyl Plank/Tile Only]	99%	≤12	30 - 60 minutes	Up to 4 hours	1 year when stored in original, unopened packaging at 73°F [23°C]	Protect from freezing	Yes	Porous/Rough Substrate: 1/16" sq. notch	Porous/Rough Substrate: 150 SF/gal
Wet/Semi-Wet Adhesive Installations	95%	≤ 11	N/A	Up to 30 minutes				Non-Porous/ Smooth Substrate: 1/16" x 1/32" x 1/32" U-Notch	Non-Porous/ Smooth Substrate: 210 SF/gal

* Varies based on temperature, humidity, substrate porosity, trowel size, and jobsite conditions.